



Underground Storage Tanks

dipstick calibration charts for 8 ft. dia. C-5 Conroe, Texas Tanks

Tanks installed level

Dipstick Reading	Tank Size and Capacity in Gallons					Dipstick Reading	Tank Size and Capacity in Gallons				
	4,000	6,000	8,000	10,000	12,000		4,000	6,000	8,000	10,000	12,000
1"	6	9	12	16	20	47"	2254	2967	3943	4919	6058
2"	16	25	35	46	57	48"	2215	3050	4053	5055	6224
3"	31	46	65	84	106	49"	2276	3133	4162	5190	6390
4"	48	72	101	130	164	50"	2337	3216	4271	5326	6556
5"	68	102	142	182	229	51"	2399	3299	4380	5461	6722
6"	91	135	188	240	302	52"	2459	3382	4489	5596	6887
7"	116	171	237	303	380	53"	2520	3464	4597	5730	7052
8"	143	210	291	371	465	54"	2581	3547	4705	5864	7216
9"	173	252	348	444	555	55"	2641	3628	4813	5998	7380
10"	204	297	409	520	651	56"	2701	3710	4920	6131	7543
11"	237	344	473	601	751	57"	2761	3791	5027	6263	7705
12"	272	394	539	685	855	58"	2820	3871	5133	6394	7866
13"	309	445	609	773	964	59"	2879	3951	5238	6524	8026
14"	347	499	681	864	1077	60"	2937	4030	5342	6654	8184
15"	387	555	756	958	1193	61"	2994	4108	5445	6782	8342
16"	428	613	834	1055	1313	62"	3051	4186	5548	6909	8498
17"	471	672	914	1155	1437	63"	3108	4263	5649	7035	8652
18"	515	734	996	1258	1563	64"	3163	4339	5749	7159	8805
19"	561	797	1080	1363	1693	65"	3218	4413	5848	7282	8956
20"	607	861	1166	1471	1826	66"	3272	4487	5945	7404	9105
21"	655	927	1254	1580	1961	67"	3325	4560	6042	7524	9252
22"	704	995	1344	1693	2099	68"	3377	4631	6136	7642	9397
23"	755	1064	1435	1807	2240	69"	3428	4702	6230	7758	9540
24"	806	1134	1529	1923	2383	70"	3479	4771	6321	7872	9681
25"	858	1206	1623	2041	2528	71"	3528	4838	6411	7984	9819
26"	911	1279	1720	2161	2675	72"	3576	4904	6499	8094	9954
27"	965	1352	1817	2282	2824	73"	3622	4969	6585	8202	10087
28"	1020	1427	1916	2405	2975	74"	3668	5032	6669	8307	10217
29"	1075	1503	2016	2530	3128	75"	3712	5094	6751	8409	10344
30"	1132	1580	2118	2655	3283	76"	3755	5153	6831	8509	10467
31"	1189	1657	2220	2782	3439	77"	3796	5211	6909	8606	10587
32"	1246	1736	2323	2911	3596	78"	3836	5267	6984	8701	10704
33"	1305	1815	2428	3040	3755	79"	3874	5321	7056	8792	10816
34"	1363	1895	2533	3170	3915	80"	3911	5372	7126	8879	10925
35"	1422	1975	2638	3302	4076	81"	3946	5422	7193	8963	11030
36"	1482	2056	2745	3434	4238	82"	3979	5469	7256	9044	11130
37"	1542	2137	2852	3567	4400	83"	4010	5513	7317	9121	11225
38"	1602	2219	2960	3700	4564	84"	4040	5555	7374	9193	11315
39"	1663	2301	3068	3834	4728	85"	4067	5595	7428	9261	11400
40"	1724	2384	3176	3969	4893	86"	4092	5631	7478	9324	11479
41"	1785	2467	3285	4104	5058	87"	4115	5664	7523	9382	11551
42"	1846	2549	3394	4239	5224	88"	4135	5694	7564	9434	11617
43"	1907	2632	3503	4374	5390	89"	4152	5719	7600	9480	11674
44"	1968	2715	3612	4510	5556	90"	4167	5741	7630	9519	11723
45"	2029	2798	3722	4645	5722	91"	4177	5757	7653	9548	11760
46"	2092	2883	3833	4782	5890	92"	4183	5766	7665	9564	11780

Non-Corrosive Products Division, Owens-Corning Fiberglas Corporation, Fiberglas Tower, Toledo, Ohio 43659

Houston Regional Office: 1107, 500 Jefferson Bldg., Houston, Texas 77002 (713) [redacted]